



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/014480 A1

- (51) **International Patent Classification⁷:** C01B 37/02,
G21K 1/06

(21) **International Application Number:**
PCT/JP2004/011582

(22) **International Filing Date:** 5 August 2004 (05.08.2004)

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) **Priority Data:**
2003-290535 8 August 2003 (08.08.2003) JP
2004-029350 5 February 2004 (05.02.2004) JP

(71) **Applicant (for all designated States except US):** CANON
KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko,
Ohta-ku, Tokyo 1468501 (JP).

(72) **Inventors; and**


(75) **Inventors/Applicants (for US only):** MIYATA, Hi-
rokatsu [JP/JP]; c/o CANON KABUSHIKI KAISHA,
3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501
(JP). KAWASHIMA, Yasuhiro [JP/JP]; c/o CANON
KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku,
Tokyo 1468501 (JP). KURODA, Kazuyuki [JP/JP]; c/o
Waseda University, 3-4-1, Okubo, Shinjuku-ku, Tokyo
1698555 (JP).

(74) **Agents:** OKABE, Masao et al.; No. 602, Fuji Bldg., 2-3,
Marunouchi 3-chome, Chiyoda-ku, Tokyo 1000005 (JP).

(81) **Designated States (unless otherwise indicated, for every
kind of national protection available):** AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

- (54) Title: MESOSTRUCTURED FILM, MESPOROUS MATERIAL FILM, AND PRODUCTION METHODS FOR THE SAME



(57) Abstract: A mesostructured film is provided having a structure in which surfactant molecular assemblies are regularly arranged three-dimensionally. A polymer compound thin film is formed on the substrate surface through spin coating or the like, and a rotating roller wrapped with a cloth is pressed against the polymer film for rubbing in one direction. The polymer material includes polyimide, polyamide, and polystyrene. The substrate includes a silica glass substrate and a silicon substrate. The mesostructured film can be formed by retaining the substrate in an aqueous solution containing a surfactant, silicon alkoxide, and acid. After being retained in the solution, the substrate is heated at about 60 to 120°C for several hours to several days for reaction. The surfactant includes $C_{18}H_{37}(OCH_2CH_2)_{20}OH$ and $C_{16}H_{33}(OCH_2CH_2)_{20}OH$. The alkoxide included tetraethoxysilane, tetramethoxysilane, and tetrapropoxysilane. Hydrochloric acid, nitric acid, or sulfuric acid is used as a catalyst.



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*